



Eco Prim T



Solvent free acrylic primer in water dispersion with very low emission of volatile organic compounds (VOC)



WHERE TO USE

All-purpose primer for interiors to improve adhesion of levelling compounds on all absorbent and non-absorbent surfaces.

Some application examples

- To prepare very compact and smooth cementitious renders and concrete floors before the application of MAPEI levelling products (see products for substrate preparation).
- To prepare surfaces with traces of glue or old existing smoothing compounds before smoothing or applying cementitious adhesives.
- Preparation of surfaces in gypsum, anhydrite, wood, marine plywood chipboard, ceramic or natural stone before smoothing or applying cementitious adhesives.
- Bonding aid for cementitious smoothing compounds on substrates consolidated or waterproofed with **Eco Prim PU 1K**, **Eco Prim PU1K Turbo**, **Primer MF** or **Primer MF EC Plus** when the surface has not been sprinkled with sand.

TECHNICAL CHARACTERISTICS

Eco Prim T is a solvent-free, easily applied acrylic resins-based primer in water dispersion. It has excellent bonding, flexibility, water and ageing resistant characteristics.

Eco Prim T is an easily applied, ready to use white coloured liquid. It is applied by brush or roller.

Eco Prim T is not flammable and shows a very low emission of volatile organic compounds (EMICODE EC1), so it is absolutely harmless to the health of the installer and the end-user. It can be stored with no particular precautions.

RECOMMENDATIONS

- Apply **Eco Prim T** only on internal flooring.
- Use **Primer EP** or **Mapeprim SP** on magnesium substrates.
- Apply **Eco Prim T** only on moisture-stable wood.
- Do not apply **Eco Prim T** on substrates subject to rising damp.

APPLICATION PROCEDURE

Preparing the substrate

Substrates must be uniformly dry, sound, free of dust, loose particles, cracks, paint, wax, oil, rust, traces of gypsum or other products that can interfere with bonding.

The regulations of each country must be strictly followed.

It is essential to make sure there is no rising damp present.

Unbonded screeds laid onto light-weight concrete or thermal-acoustic insulating layer and screeds over bare ground must be provided with a vapour barrier to prevent rising damp.

TECHNICAL DATA (typical values)	
PRODUCT IDENTIFICATION	
Consistency:	fluid liquid
Colour:	white
Density (g/cm³):	1.03
pH:	7.5
Dry solids content (%):	43
Brookfield viscosity (mPa·s):	3,000 (# 3 - 5 rpm)
Storage:	12 months in original sealed packaging. Protect from frost
Hazard classification according to EC 1999/45:	none. Before using refer to the "Safety instructions for preparation and application" paragraph and the information on the packaging and Safety Data Sheet
EMICODE:	EC1 - very low emission
Custom class:	3903 90 00
APPLICATION DATA (at +23°C - 50% R.H.)	
Application temperature range:	from +5°C to +35°C
Drying time: - concrete-wood: - ceramic:	15-20 mins. 30-40 mins.
Waiting time before applying the adhesive or the smoothing compound over: - concrete-wood: - ceramic:	2-3 hrs. 4-5 hrs.
FINAL PERFORMANCE DATA	
Resistance to moisture:	excellent
Resistance to ageing:	excellent
Resistance to solvents and oils:	fair
Resistance to acids and alkali:	fair
Resistance to temperature:	excellent

APPLYING THE PRIMER

Eco Prim T can be applied with a brush or roller. It is usually diluted 1 to 2 with water when applying on cementitious or anhydrite surfaces. It is used undiluted on existing ceramic tile, natural stone, wood and adhesive residues (as long as they are water resistant).

When the adhesive is completely dry it is possible to apply a smoothing compound or mortar. Drying time varies with the absorbency of the substrate and environmental conditions (temperature and humidity) approximately between 2 and 5 hours.

However, it is recommended not to wait more than 24 hours.

If the product is used as a bonding aid for cementitious smoothing compounds on substrates treated with an epoxy or polyurethane primer (such as **Primer MF**, **Primer MF EC Plus**, **Eco Prim PU 1K** or **Eco Prim PU1K Turbo**) and the surface has not been sprinkled with sand, **Eco Prim T** must be applied neat at least 24 hours and no more than 7 days after applying one of the above primers.

Cleaning

While still wet, **Eco Prim T** can be cleaned from floors or wall coverings, tools, hands and clothing with water. When dry, use alcohol or **Pulicol**.

CONSUMPTION

Consumption varies from 0.10 to 0.20 kg/m², depending on the porosity of the substrate and on how it is applied.

PACKAGING

Eco Prim T is available in 20 and 5 kg drums.

STORAGE

Under normal conditions **Eco Prim T** is stable for at least 24 months in its original sealed packaging. Avoid prolonged exposure to frost.

SAFETY INSTRUCTIONS FOR PREPARATION AND APPLICATION

Eco Prim T is not hazardous according to the regulations on the classification of mixtures. It is recommended to take the usual precautions for handling chemical products. For further and complete information about a safety use of our product please refer to our latest version of the Material Safety Data Sheet.

FOR PROFESSIONAL USE.

WARNING

Although the technical details and recommendations contained in this data sheet correspond to the best of our knowledge and experience, all the above information must, in every case, be taken as merely indicative and subject to confirmation after long-term practical application; for this reason, anyone who intends to use the product must ensure beforehand that it is suitable for the envisaged application. In every case, the user alone, is fully responsible for any consequences deriving from the use of the product.

Please refer to the current version of the Technical Data Sheet, available from our web site www.mapei.com



This symbol is used to identify Mapei products which give off a low level of volatile organic compounds (VOC) as certified by GEV (Gesellschaft Emissionskontrollierte Verlegewerkstoffe, Klebstoffe und Bauprodukte e.V.), an international organisation for controlling the level of emissions from products used for floors.



Our Commitment To The Environment
More than 150 MAPEI products assist Project Designers and Contractors create innovative LEED (The Leadership in Energy and Environmental Design) certified projects, in compliance with the U.S. Green Building Council.

All relevant references for the product are available upon request and from www.mapei.com



Eco-Prim T



Any reproduction of texts, photos and illustrations published here is prohibited and subject to prosecution

2908-7-2010

(GB) A.G. BETA