



# Ultracoat Oil Care

**Natural drying oil-based resin finish in water dispersion for wooden floors treated with oil**



## WHERE TO USE

Final finishing treatments and routine maintenance of wooden floors treated with **Ultracoat Oil**.  
Repairing small scratches made during laying operations on new wooden floors.

## TECHNICAL CHARACTERISTICS

**Ultracoat Oil Care** is a solvent-free, natural drying oil in water dispersion for final finishing treatments and routine maintenance of wooden floors.

**Ultracoat Oil Care** used for routine maintenance operations helps maintain the original beauty of wooden floors as when they were originally laid.

**Ultracoat Oil Care** leaves the floor with a matt finish.

## RECOMMENDATIONS

- Do not use **Ultracoat Oil Care** at temperatures lower than +10°C.
- Do not apply on external surfaces.
- Use only clean containers and tools.
- Environmental conditions and residual humidity in the wood when it is laid must conform to current norms and standards.
- Do not put leftover quantities of the product back into its original container.

- Do not use **Ultracoat Oil Care** for maintenance on wooden floors treated with oil which have a matt or grey appearance. In such cases, apply a coat of **Ultracoat Oil** beforehand.

## APPLICATION PROCEDURE

### Preparation of the substrate

Final treatment of wooden floors after applying **Ultracoat Oil**.

Wooden surfaces treated prior to application with **Ultracoat Oil** must be clean, dry and free of dust.

### Routine maintenance of wooden floors treated with oil

Wooden surfaces treated with oil must be clean, dry and free of dust.

Uneven or rough areas on the surface may be removed by passing over with a rotating head fitted with a black **Ultracoat Pad** or by light sanding. In such cases, if the whole of the surface is not covered with a priming coat of **Ultracoat Oil**, apply another coat of the product with an **Ultracoat Roller Plus** or an **Ultracoat Steel Spatula**. Within 60 minutes of spreading on the product remove excess oil with a cotton rag with the aid of a rotating head fitted with a white **Ultracoat Pad**.

### Application

16 hours after spreading on **Ultracoat Oil** (in those cases where it has been applied) pass over the surface of the wood with a brush fitted with a black **Ultracoat Pad**. Then apply two coats of **Ultracoat Oil Care** 30 minutes apart using a wax spreader or



# Ultracoat Oil Care



## TECHNICAL DATA (typical values)

### PRODUCT IDENTITY

Consistency:	fluid
Colour:	whitish
Density (g/cm <sup>3</sup> ):	1,0
Storage:	24 months
Hazard classification according to EC 1999/45	none. Before using refer to the "Safety instructions for preparation and application" paragraph and the information on the packaging and Safety Data Sheet
Customs class:	3209 90 00

### APPLICATION DATA (at +23°C - 50% R.H.)

Drying time:	30-60 minutes
Set to light foot traffic:	1 hour
Waiting time before putting into service:	3 days

rotating head fitted with a white **Ultracoat Pad** and a cotton rag.

#### Cleaning

Tools and residues of **Ultracoat Oil Care** may be cleaned with water while the product is still fresh.

#### CONSUMPTION

Absorbent floors: approx. 15 g/m<sup>2</sup>.

#### PACKAGING

5 litre canisters.

#### STORAGE

24 months in its original, sealed packaging in a dry place.

#### SAFETY INSTRUCTIONS FOR PREPARATION AND INSTALLATION

**Ultracoat Oil Care** is not considered hazardous according to current norms and guidelines regarding the classification of preparations. However, we recommend the use of protective gloves and goggles, and to take the usual precautions for handling chemical products.

Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. To avoid the risks of fires, all contaminated materials should be stored in metal containers with tight-fitting self-closing lids. Contaminated materials should be stored outside.

For further and complete information about a safety use of our product please refer to our latest version of the Material Safety Data Sheet.

FOR PROFESSIONAL USE.

#### WARNING

*Although the technical details and recommendations contained in this product data sheet correspond to the best of our knowledge and experience, all the above information must, in every case, be taken as merely indicative and subject to confirmation after long-term practical applications. For this reason, anyone who intends using the product must ensure beforehand that it is suitable for the envisaged application. In every case, the user alone is fully responsible for any consequences deriving from the use of the product.*

**Please refer to the current version of the Technical Data Sheet, available from our web site [www.mapei.com](http://www.mapei.com)**



**All relevant references for the product are available upon request and from [www.mapei.com](http://www.mapei.com)**

