



# Ultracoat Clean WPM

**Product for the maintenance and protection of wooden floors varnished with matt or extra matt finish**



## **MAINTENANCE**

**Ultracoat Clean WPM** is a ready-to-use product which may be diluted according to requirements. It has been specially developed for the maintenance of residential and commercial wooden floors varnished with the water-based varnishes of the **Ultracoat** line.

It increases the level of protection of floors against wear, covers light, surface scratches and leaves surfaces with a new, shiny finish.

- Developed specifically for treating wooden floors coated with the water-based paints of the **Ultracoat** line.
- Suitable for both domestic and commercial environments.
- Covers superficial scratches.
- Increases the level of protection against wear.
- High resistance to scratches caused by footsteps.
- No polishing required.

### **Cleaning and maintenance of floors with a low volume of traffic**

Before applying the product, the surfaces to be

treated must be thoroughly cleaned to remove all traces of dirt, dust, etc. Use **Ultracoat Universal Cleaner** for final cleaning.

Dilute 100 ml of **Ultracoat Clean WPM** with 10 litres of water and apply an even coat on the floor with a clean micro-fibre applicator or a well-wrung cloth.

### **Cleaning and maintenance of floors with a high volume of traffic and covering light surface scratches**

Before applying the product, the surfaces to be treated must be thoroughly cleaned to remove all traces of dirt, dust, etc. Use **Ultracoat Universal Cleaner** to completely clean the surface so that a good adhesion is formed with the **Ultracoat Clean WPM**.

On floors with a high volume of traffic varnished with the water-based paints of the **Ultracoat** line, we recommend using undiluted **Ultracoat Clean WPM**.

## **CONSUMPTION**

80/100 m<sup>2</sup>/litre for each coat without diluting the product. On large surfaces, we recommend using a wax-spreader machine to make application easier and to form a more durable, resistant surface.

Wait approximately 1 hour before stepping on treated surfaces. Clean tools immediately after use.

# Ultracoat Clean WPM



Example of Ultracoat Clean WPM used undiluted: apply a small quantity of product to the floor



Applying the product to the floor with a microfiber cloth

TECHNICAL DATA (typical values)	
<b>PRODUCT IDENTITY</b>	
Product:	nonionic tenside
Colour:	colorless after drying
Gloss:	ultramatt to matt
pH value:	6-8
Dilution:	for weekly cleaning use 100 ml to 10 litres of water; on high traffic floors <b>Ultracoat Clean WPM</b> is used undiluted
Application:	microfibre applicator pad or cotton cloth
Substrate temperature:	minimum +5°C
Package size:	1 litre
Consumption:	80-100 m <sup>2</sup> per litre diluted product. Approx. 20 m <sup>2</sup> per litre undiluted
Drying time:	approx. 30 minutes at a room temperature of +20°C, depending on surroundings and quantity applied
Cleaning of tools:	neutral soap and water
Scratches:	to be used undiluted
Storage:	24 months unopened and stored at +20°C. Not to be exposed to temperatures below 0°C
Hazard classification according to EC 1999/45:	none. Before using refer to the "Safety instructions for preparation and application" paragraph and the information on the packaging and Safety Data Sheet

## SAFETY INSTRUCTIONS FOR PREPARATION AND APPLICATION

Ultracoat Clean WPM is not considered hazardous according to current standards and regulations regarding the classification of mixtures. It is however recommended to use gloves, eye protection and to take the usual precaution taken when handling chemical products are recommended. For further and complete information about the safe use of our product please refer to our latest version of the Material Safety Data Sheet.

PRODUCT FOR PROFESSIONAL USE.

### WARNING

Although the technical details and recommendations contained in this product data sheet correspond to the best of our knowledge and experience, all the

above information must, in every case, be taken as merely indicative and subject to confirmation after long-term practical application: for this reason, anyone who intends to use the product must ensure beforehand that it is suitable for the envisaged application: in every case, the user alone is fully responsible for any consequences deriving from the use of the product.

Please refer to the current version of the Technical Data Sheet, available from our web site [www.mapei.com](http://www.mapei.com)

**All relevant references for the product are available upon request and from [www.mapei.com](http://www.mapei.com)**



BUILDING THE FUTURE